

(19)



JAPANESE PATENT OFFICE

PATENT ABSTRACTS OF JAPAN

(11) Publication number: **02208993 A**

(43) Date of publication of application: **20.08.90**

(51) Int. Cl. **H05K 1/02**  
**H05K 1/18**

(21) Application number: **01027568**

(22) Date of filing: **08.02.89**

(71) Applicant: **SONY CORP**

(72) Inventor: **YUSA MOTOO**  
**OSAWA MASAYUKI**

(54) **PRINTED BOARD**

board of this design is excellent in solderability.

(57) Abstract:

COPYRIGHT: (C)1990,JPO&Japio

**PURPOSE:** To obtain a printed board of excellent solderability on which the leads of an electronic component are set in position by a method wherein adjacent holes very close to each other on the board are connected to each other through a slit whose width is equal to a specified value or more and smaller than the length of minor axis of the hole.

**CONSTITUTION:** A printed board is composed of a printed board main body 1, a first and a second hole, 2 and 3, and a slit 4 which connects the holes 2 and 3 together. Here, the width *a* of the slit 4 is set larger than 0.5mm and smaller than the length of minor axis of the smaller hole (when the hole is not a right circle, the length of minor axis of the hole). In the substrate main body 1 structured as mentioned above, as the width *a* is made equal to 0.5mm or more, a die can retain its strength, where a molding die does not collapse or a punch is not broken. And, as the width *a* is made smaller than the length of short axis of the smaller hole, the slit 4 is small in width and the leads of an electronic component are set in position, and a metal foil provided around the holes is small in cutout, so that a printed

